

# **EAS**®

KING OF BATTERIES

## **KING of BATTERIES for THE KING of the ROADS!**

Neither difficult roads nor steep slopes...  
Neither the darkness of the night nor the light of the day...  
Snowy roads or sharp turns do not matter!  
If you have full energy, if you feel your inner power,  
the roads and years shall yield!

Since day one, we provide the endless energy of the kings of  
the roads with our high quality products worthy of our  
production technology that is matcing the world standards



**EFB**  
Cars and Light  
Commercial Vehicles



(1)Compared to EAS ACTIV A Series

## EFB

**EAS Start-Stop EFB** batteries have been specially designed for standard Start-Stop vehicles. Provides maintenance-free extra long life and extra performance even for new generation vehicles with high electricity consumption through its special paste formula and reinforced high-quality plates.

### Product Features

- Sealed Maintenance Free
- Double-sided flame arrestors and gas evacuation system
- Up to 2.5 times more cycle life<sup>(1)</sup>
- Special grid design strong positive plates
- Low internal resistance special separators



SHORT CODE	GREEN CODE	EN	DIN	CODE BCI	JIS**	BOX TYPE	DIMENSIONS LENGTHx WIDTHx HEIGHT (mm)	C20 CAPACITY (Ah)	CCA - EN	CCA - SAE*	RESERVE CAPACITY RC	LAYOUT	TERMINAL TYPE	HOLD-DOWN	
<b>Passenger &amp; Light Commercial</b>							<b>Start-Stop EFB</b>								
LB2 060 056 013	2009890	L2B	T5	90	---	LB2	242*175*175	60	560A	600A	98	0	1	B13	
L2 060 056 013	2008966	LN2	H5	47	---	L2	242*175*190	60	560A	600A	98	0	1	B13	
L3 072 068 013	2008980	LN3	H6	48	---	L3	278*175*190	72	680A	730A	121	0	1	B13	
L4 080 073 013	2008992	LN4	H7	94R	---	L4	315*175*190	80	730A	780A	137	0	1	B13	
L5 090 083 013	2009073	LN5	H8	49	---	L5	352*175*190	90	830A	890A	158	0	1	B13	
D23 065 062 010	2008819	---	---	35	65D23L	D23	232*173*225	65	---	620A	107	0	1	B00	
D26 072 076 017	2008821	---	---	24R	75D26L	D26	264*175*225	72	---	760A	121	0	1	B07	



(1) Compared to EAS ACTIV A Series

\*CCA-SAE value is based on tester flooded mode value.

\*\*JIS definition is selected from JIS standard based on the closest capacity value.